

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Previously amended) A connecting construction for components of a system frame, comprising:

- a framework having frame struts and a cross bracket connecting the frame struts,
- a sheet steel corner plate which is arranged in each case in the region in which the cross bracket is connected to the frame strut and which has a corner recess in the corner region of the plate in which the cross bracket is connected to the frame strut,
- a coupling unit that is connectable to the frame strut via the sheet steel corner plate,
- a further recess in the sheet steel corner plate approximately level with the corner recess and offset inward,
- a further coupling unit having a first coupling element and a second coupling element,
- wherein the first coupling element is connectable to a frame tube,
- wherein the second coupling element is fastenable in the further recess of the sheet steel corner plate with at least one of a positive and non-positive fit, and has a spacer profile and a projecting profile arranged on the free end side of the spacer profile said projecting profile being connectable in the further recess of the sheet steel corner plate with at least one of a positive and/or and non-positive fit.

3. (Previously amended) The connecting construction as claimed in claim 2, the projecting profile is a hammer head and the further recess (24) is a slot so that in order to connect the further coupling unit (30) to the sheet steel corner plate, the projecting profile can be introduced into the further recess (24) as far as the stop of the spacer profile and the at least one of a positive and non-positive fit is produced by rotation of the further coupling unit by said rotation causing the hammer head of the projecting profile (38) to engage at least in some area behind the sheet steel corner plate (20).

4. (Previously amended) The connecting construction as claimed in claim 3, wherein the slot is arranged vertically upright.

5. (Previously amended) The connecting construction as claimed in claim 3, wherein the slot is arranged horizontally.

6. (Previously amended) The connecting construction as claimed in claim 13, wherein the further recess is arranged spaced apart from the lower edge of the cross bracket .

7. (Previously amended) The connecting construction as in claim 13, wherein the first coupling element of the further coupling unit is a tube half-coupling.

8. (Previously amended) The connecting construction as in claim 13, wherein the further coupling unit is a single-piece metal cast part.

9. (Previously amended) The connecting construction as in claim 13, wherein the length of the projecting profile is selected in such a manner that the clear distance of a frame tube, which is connected parallel to the cross bracket in the first coupling element of the further coupling unit, from the sheet steel corner plate is greater than the length of the maximum projecting length relative to the sheet steel corner plate of a coupling unit arranged in the corner recess.

10. (Withdrawn) The connecting construction as claimed in claims 1 to 3, characterized in that

- a rotation prevention unit is provided which secures the further coupling unit (30) against rotation in a position in which it is connected to the sheet steel corner plate (20).

11. (Previously amended) The connecting construction as in claim 13, wherein the further recess of the sheet steel corner plate has a cross-sectional deformation (68) pointing out of the plane of the sheet steel corner plate.

12. (Previously amended) The connecting construction as claimed in claim 11, wherein the cross-sectional deformation is provided encircling the further recess .

13. (Previously amended) A connecting construction for components of a system frame in a scaffolding, comprising:

- a framework having frame struts and a cross bracket connecting the frame struts,
- a sheet steel corner plate which is arranged in each case in the region in which the cross bracket is connected to the frame strut and which has a corner recess in the corner region of the plate in which the cross bracket is connected to the frame strut,
- a coupling unit that is connectable to the frame strut via the sheet steel corner plate,
- a further recess in the sheet steel corner plate approximately level with the corner recess and offset inward,
- a further coupling unit having a first coupling element and a second coupling element, wherein the first coupling element is connectable to a frame tube, and wherein the second coupling element is fastenable in the further recess of the sheet steel corner plate with at least one of a positive and non-positive fit, and
- an additional recess provided below the corner recess of the sheet steel corner plate, and an additional coupling unit that is connectable to the frame strut via the additional recess.

14. (Previously amended) The connecting construction as claimed in claim 13, wherein the additional recess on the sheet steel corner plate is formed by a U-shaped recess which is open toward the longitudinal connecting edge of the sheet steel corner plate.

15. (Withdrawn) The connecting construction as claimed in claims 1 to 3, characterized in that

a further coupling unit (30) is connected in each case in the further recess (24) to the two sheet steel corner plates (20) of a framework (10), and the coupling units (30) are connected to a continuous frame tube (40).

wherein the second coupling element is fastenable in the further recess of a sheet steel corner plate with at least one of a positive and non-positive fit.

wherein the second coupling element is fastenable in the further recess of a sheet steel corner plate with at least one of a positive and non-positive fit, and [[-]] the second coupling element has a spacer profile and a projecting profile arranged on the free end side of the spacer profile, said projecting profile being connectable into the further recess of the sheet steel corner plate with at least one of a positive and non-positive fit.

- {W:\01954\000m900us0\00585614.DOC {XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX}}